



Axial camera

RIK-1820

Article-No. 5-0034-001 (PAL)



Technical data

Application area	DN 20 - DN 70
Suitable for 87° bends	as of DN 40*
Permanent upright picture	✗
Push operation	✓
Crawler operation	✗
Waterproof	✓ up to 1 bar
Lighting	6 LEDs
Lens	85°
Focus	fix focus (ca. 3 - 30 cm 1.2 - 11.8 in)
High-resolution color camera module	480 lines
Image sensor	1/3" Color-CMOS
Pluggable mounting	✓
Operating temperature	0° to 40° C 32° to 104° F
Storage temperature	-10° to 60° C 14° to 140° F
Material	stainless steel
Dimensions (Ø / Length)	18 / 20 mm 0.7 / 0.8 in
Weight	ca. 32 g 1.1 oz

* depending on reel

M&T INNOVATIONS (M) SDN. BHD.

No.32-2A, Jalan PJU 1/3A, Sunwaymas Commercial Centre,
47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

T : +603 7803 1145 F : +603 7803 1147

E : sales@mt-engg.com

RIEZLER Inspektionssysteme GmbH & Co. KG

Sportplatzweg 5 | 87471 Durach | Germany

Tel. +49 (831) 27714 | info@riezler.eu | www.riezler.eu